

Hamachi unter Ubuntu

Hamachi Start/Stop-Script **/etc/init.d/hamachi**

```
#!/bin/bash
#
### File: /etc/init.d/hamachi
#
### BEGIN INIT INFO
# Provides:          hamachi
# Required-Start:    none
# Required-Stop:     none
# Default-Start:     2 3 4 5
# Default-Stop:      0 1 6
# Short-Description: starts the hamachi client
# Description:       Es wird der Hamachi-VPN-Client gestartet
### END INIT INFO
# Start-Stop
case "$1" in
    start)
        echo "Starting script hamachi"
        tuncfg          PROGRAM="hamachi -c /root/.hamachi/ start"
        $PROGRAM >/dev/null &
        PID=$!
        echo $PID > /var/run/
hamachi.pid           ;;
    stop)
        if test -f /var/run/
hamachi.pid           then
            echo "Stopping script hamachi"
            PID=$(cat /var/run/hamachi.pid)
            PROGRAMSTOP="hamachi -c /root/.hamachi/ stop"
            $PROGRAMSTOP
            rm /var/run/
hamachi.pid           else
            echo "Hamachi-Daemon not running"
            fi
        ;;
    status)
        if test -f /var/run/
hamachi.pid           then
            echo "Daemon is running"
        else
            echo "Daemon not running"
        fi
    ;;
esac
```

```
restart)
    /etc/init.d/
hamachi stop      /etc/init.d/
hamachi start    ;;
*)
    echo "Usage: /etc/init.d/hamachi{start|stop|restart}"
    exit 1
    ;;
esac
exit 0
```

Hamachi ziemlich zum Ende des Startvorgangs starten und beim Herunterfahren als erstes wieder beenden.

```
sudo update-rc.d hamachi defaults 99 01
```